

pthread

Jonathan Misurda
jmisurda@cs.pitt.edu

pthread

- pthread (POSIX threads) is a library for doing threading
- Can transparently be used under User or Kernel threads

POSIX

- Portable Operating System Interface
- Standard to unify the programs and system calls that many different OSes provide.

pthread_create()

```
#include <stdio.h>
#include <pthread.h>

void *do_stuff(void *p) {
    printf("Hello from thread %d\n", *(int *)p);
}

int main() {
    pthread_t thread;
    int id, arg1, arg2;

    arg1 = 1;
    id = pthread_create(&thread, NULL, do_stuff, (void *)&arg1);
    arg2 = 2;
    do_stuff((void *)&arg2);
    return 0;
}
```

Output

Hello from thread 2

Yield!

```
#include <stdio.h>
#include <pthread.h>

void *do_stuff(void *p)
{
    printf("Hello from thread %d\n", *(int *)p);
}

int main()
{
    pthread_t thread;
    int id, arg1, arg2;

    arg1 = 1;
    id = pthread_create(&thread, NULL, do_stuff, (void *)&arg1);
    pthread_yield();
    arg2 = 2;
    do_stuff((void *)&arg2);

    return 0;
}
```

Output

Hello from thread 1
Hello from thread 2

pthread_join

```
#include <stdio.h>
#include <pthread.h>

void *do_stuff(void *p)
{
    printf("Hello from thread %d\n", *(int *)p);
}

int main()
{
    pthread_t thread;
    int id, arg1, arg2;

    arg1 = 1;
    id = pthread_create(&thread, NULL, do_stuff, (void *)&arg1);
    arg2 = 2;
    do_stuff((void *)&arg2);
    pthread_join(thread, NULL);
    return 0;
}
```

Output

Hello from thread 2
Hello from thread 1

Compile

- Need the `-pthread` option to gcc
- Links in the library

```
gcc -o threadtest threadtest.c -pthread
```

pthread_create()

```
int pthread_create(
    pthread_t *restrict thread,
    const pthread_attr_t *restrict attr,
    void *(*start_routine)(void*),
    void *restrict arg
);
```

- A unique identifier for the thread
- Thread attributes or NULL for the default
- A C Function Pointer
- The argument to pass to the function

Start Routine Prototype

```
void *(*start_routine)(void*)
```

Java Threads

```
class TestThread implements Runnable {  
    private int x;  
    public static void main(String[] args) {  
        Thread t1 = new Thread(new TestThread(1));  
        Thread t2 = new Thread(new TestThread(2));  
  
        t1.start();  
        t2.start();  
    }  
  
    public void run() {  
        System.out.println("Hello from thread " + x);  
    }  
  
    public TestThread(int y) { x = y; }  
}
```

Output

Hello from thread 1
Hello from thread 2