

Inference in first-order logic

Chapter 9

Outline

- Reducing first-order inference to propositional inference
- Unification
- Generalized Modus Ponens
- Forward chaining
- Backward chaining
- Resolution

Inference with Quantifiers

- Universal Instantiation:
 - Given $\forall X \text{ person}(X) \Rightarrow \text{likes}(X, \text{sun})$
 - Infer $\text{person}(\text{john}) \Rightarrow \text{likes}(\text{john}, \text{sun})$
- Existential Instantiation:
 - Given $\exists x \text{ likes}(x, \text{chocolate})$
 - Infer: $\text{likes}(S1, \text{chocolate})$
 - S1 is a “Skolem Constant” that is not found anywhere else in the KB and refers to (one of) the individuals that likes sun.

Universal instantiation (UI)

- Every instantiation of a universally quantified sentence is entailed by it:

$$\frac{\forall v \alpha}{\text{Subst}(\{v/g\}, \alpha)}$$

for any variable v and ground term g

- E.g., $\forall x \text{ King}(x) \wedge \text{Greedy}(x) \Rightarrow \text{Evil}(x)$ yields:
 - $\text{King}(\text{John}) \wedge \text{Greedy}(\text{John}) \Rightarrow \text{Evil}(\text{John})$
 - $\text{King}(\text{Richard}) \wedge \text{Greedy}(\text{Richard}) \Rightarrow \text{Evil}(\text{Richard})$
 - $\text{King}(\text{Father}(\text{John})) \wedge \text{Greedy}(\text{Father}(\text{John})) \Rightarrow \text{Evil}(\text{Father}(\text{John}))$
 -
 -
 -

Existential instantiation (EI)

- For any sentence α , variable v , and constant symbol k that does **not** appear elsewhere in the knowledge base:

$$\frac{\exists v \alpha}{\text{Subst}(\{v/k\}, \alpha)}$$

- E.g., $\exists x \text{Crown}(x) \wedge \text{OnHead}(x, \text{John})$ yields:

$$\text{Crown}(C_1) \wedge \text{OnHead}(C_1, \text{John})$$

provided C_1 is a new constant symbol, called a **Skolem constant**

Reduction to propositional inference

Suppose the KB contains just the following:

$\forall x \text{King}(x) \wedge \text{Greedy}(x) \Rightarrow \text{Evil}(x)$
 $\text{King}(\text{John})$
 $\text{Greedy}(\text{John})$
 $\text{Brother}(\text{Richard}, \text{John})$

- Instantiating the universal sentence in **all possible** ways, we have:

$\text{King}(\text{John}) \wedge \text{Greedy}(\text{John}) \Rightarrow \text{Evil}(\text{John})$
 $\text{King}(\text{Richard}) \wedge \text{Greedy}(\text{Richard}) \Rightarrow \text{Evil}(\text{Richard})$
 $\text{King}(\text{John})$
 $\text{Greedy}(\text{John})$
 $\text{Brother}(\text{Richard}, \text{John})$

- The new KB is **propositionalized**: proposition symbols are

$\text{King}(\text{John}), \text{Greedy}(\text{John}), \text{Evil}(\text{John}), \text{King}(\text{Richard}), \text{etc.}$

□

Reduction contd.

- Every FOL KB can be propositionalized so as to preserve entailment
- (A ground sentence is entailed by new KB iff entailed by original KB)
- Idea: propositionalize KB and query, apply resolution, return result
- Problem: with function symbols, there are infinitely many ground terms,
 - e.g., $Father(Father(Father(John)))$

Reduction contd.

Theorem: Herbrand (1930). If a sentence α is entailed by an FOL KB, it is entailed by a **finite** subset of the propositionalized KB

Idea: For $n = 0$ to ∞ do
create a propositional KB by instantiating with depth- n terms
see if α is entailed by this KB

Problem: works if α is entailed, loops if α is not entailed

Theorem: Turing (1936), Church (1936) Entailment for FOL is **semidecidable** (algorithms exist that say yes to every entailed sentence, but no algorithm exists that also says no to every nonentailed sentence.)

Problems with propositionalization

- Propositionalization seems to generate lots of irrelevant sentences.
- E.g., from:
 - $\forall x \text{ King}(x) \wedge \text{Greedy}(x) \Rightarrow \text{Evil}(x)$
 - $\text{King}(\text{John})$
 - $\forall y \text{ Greedy}(y)$
 - $\text{Brother}(\text{Richard}, \text{John})$
- it seems obvious that $\text{Evil}(\text{John})$, but propositionalization produces lots of facts such as $\text{Greedy}(\text{Richard})$ that are irrelevant
- With p k -ary predicates and n constants, there are $p \cdot n^k$ instantiations.

Unification

- We can get the inference immediately if we can find a substitution θ such that $\text{King}(x)$ and $\text{Greedy}(x)$ match $\text{King}(\text{John})$ and $\text{Greedy}(y)$

$\theta = \{x/\text{John}, y/\text{John}\}$ works

- $\text{Unify}(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
$\text{Knows}(\text{John}, x)$	$\text{Knows}(\text{John}, \text{Jane})$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{OJ})$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(y, \text{Mother}(y))$	
$\text{Knows}(\text{John}, x)$	$\text{Knows}(x, \text{OJ})$	

- [Standardizing apart](#) eliminates overlap of variables, e.g., $\text{Knows}(z_{17}, \text{OJ})$

Unification

- We can get the inference immediately if we can find a substitution θ such that $King(x)$ and $Greedy(x)$ match $King(John)$ and $Greedy(y)$

$\theta = \{x/John, y/John\}$ works

- $Unify(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
Knows(John,x)	Knows(John,Jane)	{x/Jane}
Knows(John,x)	Knows(y,OJ)	
Knows(John,x)	Knows(y,Mother(y))	
Knows(John,x)	Knows(x,OJ)	

- Standardizing apart eliminates overlap of variables, e.g., $Knows(z_{17}, OJ)$

Unification

- We can get the inference immediately if we can find a substitution θ such that $King(x)$ and $Greedy(x)$ match $King(John)$ and $Greedy(y)$

$\theta = \{x/John, y/John\}$ works

- $Unify(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
Knows(John,x)	Knows(John,Jane)	{x/Jane} {x/OJ, y/John}
Knows(John,x)	Knows(y,OJ)	
Knows(John,x)	Knows(y,Mother(y))	
Knows(John,x)	Knows(x,OJ)	

- Standardizing apart eliminates overlap of variables, e.g., $Knows(z_{17}, OJ)$

Unification

- We can get the inference immediately if we can find a substitution θ such that $King(x)$ and $Greedy(x)$ match $King(John)$ and $Greedy(y)$

$\theta = \{x/John, y/John\}$ works

- $Unify(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
Knows(John,x)	Knows(John,Jane)	{x/Jane}
Knows(John,x)	Knows(y,OJ)	{x/OJ,y/John}
Knows(John,x)	Knows(y,Mother(y))	{y/John,x/Mother(John)}
Knows(John,x)	Knows(x,OJ)	

- Standardizing apart eliminates overlap of variables, e.g.,
Knows(z₁₇,OJ)

Unification

- We can get the inference immediately if we can find a substitution θ such that $King(x)$ and $Greedy(x)$ match $King(John)$ and $Greedy(y)$

$\theta = \{x/John, y/John\}$ works

- $Unify(\alpha, \beta) = \theta$ if $\alpha\theta = \beta\theta$

p	q	θ
Knows(John,x)	Knows(John,Jane)	{x/Jane}
Knows(John,x)	Knows(y,OJ)	{x/OJ,y/John}
Knows(John,x)	Knows(y,Mother(y))	{y/John,x/Mother(John)}
Knows(John,x)	Knows(x,OJ)	{fail}

- Standardizing apart eliminates overlap of variables, e.g.,
Knows(z₁₇,OJ)

More on Standardizing apart

- $\text{knows}(\text{john}, X)$.
- $\text{knows}(X, \text{elizabeth})$.
- These ought to unify, since john knows everyone, and everyone knows elizabeth.
- Rename variables to avoid such name clashes

Note:

$$\text{all } X \text{ } p(X) == \text{all } Y \text{ } p(Y)$$

$$\text{All } X (p(X) \wedge q(X)) == \text{All } X \text{ } p(X) \wedge \text{All } Y \text{ } p(Y)$$

Unification

- To unify $\text{Knows}(\text{John}, x)$ and $\text{Knows}(y, z)$,
 $\theta = \{y/\text{John}, x/z\}$ or $\theta = \{y/\text{John}, x/\text{John}, z/\text{John}\}$
- The first unifier is **more general** than the second.
- There is a single **most general unifier** (MGU) that is unique up to renaming of variables.
 $\text{MGU} = \{y/\text{John}, x/z\}$

Generalized Modus Ponens

- This is a general inference rule for FOL that does not require instantiation
- GMP “lifts” MP from propositional to first-order logic
- Key advantage of lifted inference rules over propositionalization is that they make only substitutions which are required to allow particular inferences to proceed

Example knowledge base

- The law says that it is a crime for an American to sell weapons to hostile nations. The country Nono, an enemy of America, has some missiles, and all of its missiles were sold to it by Colonel West, who is American.
- Prove that Col. West is a criminal

Example knowledge base contd.

... it is a crime for an American to sell weapons to hostile nations:

$American(x) \wedge Weapon(y) \wedge Sells(x,y,z) \wedge Hostile(z) \Rightarrow Criminal(x)$

Nono ... has some missiles, i.e., $\exists x Owns(Nono,x) \wedge Missile(x)$:

$Owns(Nono,M_1)$ and $Missile(M_1)$

... all of its missiles were sold to it by Colonel West

$Missile(x) \wedge Owns(Nono,x) \Rightarrow Sells(West,x,Nono)$

Missiles are weapons:

$Missile(x) \Rightarrow Weapon(x)$

An enemy of America counts as "hostile":

$Enemy(x,America) \Rightarrow Hostile(x)$

West, who is American ...

$American(West)$


The country Nono, an enemy of America ...

$Enemy(Nono,America)$ □


Another Example

- $\forall x,y,z \text{ parent}(x,y) \wedge \text{parent}(y,z) \Rightarrow \text{grandparent}(x,z)$
- $\text{parent}(\text{james}, \text{john}), \text{parent}(\text{james}, \text{richard}), \text{parent}(\text{harry}, \text{james})$
- We can derive:
 - $\text{Grandparent}(\text{harry}, \text{john})$, bindings:
 $\{x/\text{harry}, y/\text{james}, z/\text{john}\}$
 - $\text{Grandparent}(\text{harry}, \text{richard})$, bindings:
 $\{x/\text{harry}, y/\text{james}, z/\text{richard}\}$


Forward chaining proof



Forward chaining proof



Forward chaining proof



Properties of forward chaining

- Sound and complete for first-order definite clauses
- **Datalog** = first-order definite clauses + **no functions**
- FC terminates for Datalog in finite number of iterations
- May not terminate in general if α is not entailed
- This is unavoidable: entailment with definite clauses is semidecidable

Efficiency of forward chaining

Incremental forward chaining: no need to match a rule on iteration k if a premise wasn't added on iteration $k-1$

⇒ match each rule whose premise contains a newly added positive literal

Matching itself can be expensive:

Database indexing allows $O(1)$ retrieval of known facts


– e.g., query $Missile(x)$ retrieves $Missile(M_1)$

Forward chaining is widely used in deductive databases


Backward chaining example

Criminal(West)


Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example



Backward chaining example



Backward chaining example



Properties of backward chaining

- Depth-first recursive proof search: space is linear in size of proof
- Incomplete due to infinite loops
 - \Rightarrow fix by checking current goal against every goal on stack
- Inefficient due to repeated subgoals (both success and failure)
 - \Rightarrow fix using caching of previous results (extra space)
- Widely used for [logic programming](#)

Resolution: brief summary

- Full first-order version:

$$\frac{l_1 \vee \dots \vee l_k, \quad m_1 \vee \dots \vee m_n}{(l_1 \vee \dots \vee l_{i-1} \vee l_{i+1} \vee \dots \vee l_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n)\theta}$$

where $\text{Unify}(l_i, \neg m_j) = \theta$.

- The two clauses are assumed to be standardized apart so that they share no variables.
- For example,

$$\frac{\neg \text{Rich}(x) \vee \text{Unhappy}(x)}{\text{Rich}(\text{Ken})} \\ \hline \text{Unhappy}(\text{Ken})$$

with $\theta = \{x/\text{Ken}\}$

- Apply resolution steps to $\text{CNF}(\text{KB} \wedge \neg\alpha)$; complete for FOL


Conversion to CNF

- Everyone who loves all animals is loved by someone:
 $\forall x [\forall y \text{Animal}(y) \Rightarrow \text{Loves}(x,y)] \Rightarrow [\exists y \text{Loves}(y,x)]$
- 1. Eliminate biconditionals and implications
 $\forall x [\neg \forall y \neg \text{Animal}(y) \vee \text{Loves}(x,y)] \vee [\exists y \text{Loves}(y,x)]$
- 2. Move \neg inwards: $\neg \forall x p \equiv \exists x \neg p$, $\neg \exists x p \equiv \forall x \neg p$
 $\forall x [\exists y \neg(\neg \text{Animal}(y) \vee \text{Loves}(x,y))] \vee [\exists y \text{Loves}(y,x)]$
 $\forall x [\exists y \neg \neg \text{Animal}(y) \wedge \neg \text{Loves}(x,y)] \vee [\exists y \text{Loves}(y,x)]$
 $\forall x [\exists y \text{Animal}(y) \wedge \neg \text{Loves}(x,y)] \vee [\exists y \text{Loves}(y,x)]$

Conversion to CNF contd.

3. Standardize variables: each quantifier should use a different one
 $\forall x [\exists y \text{ Animal}(y) \wedge \neg \text{Loves}(x,y)] \vee [\exists z \text{ Loves}(z,x)]$
4. Skolemize: a more general form of existential instantiation.
 Each existential variable is replaced by a **Skolem function** of the enclosing universally quantified variables:
 $\forall x [\text{Animal}(F(x)) \wedge \neg \text{Loves}(x,F(x))] \vee \text{Loves}(G(x),x)$
5. Drop universal quantifiers:
 $[\text{Animal}(F(x)) \wedge \neg \text{Loves}(x,F(x))] \vee \text{Loves}(G(x),x)$
6. Distribute \vee over \wedge :
 $[\text{Animal}(F(x)) \vee \text{Loves}(G(x),x)] \wedge [\neg \text{Loves}(x,F(x)) \vee \text{Loves}(G(x),x)]$

Resolution proof: definite clauses



- Resolution is complete. If you don't want to take this on faith, study pp. 300-303
- Strategies (heuristics) for efficient resolution include
 - Unit preference. If a clause has only one literal, use it first.
 - Set of support. Identify “useful” rules and ignore the rest. (p. 305)
 - Input resolution. Intermediately generated sentences can only be combined with original inputs or original rules.
 - Subsumption. Prune unnecessary facts from the database.

Inference Methods (Review)

- Unification (prerequisite)
- Forward Chaining
 - Production Systems
- Backward Chaining
 - Logic Programming (Prolog)
- Resolution
 - Transform to CNF
 - Generalization of Prop. Logic resolution